

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES PATENT

**TRANSIENT SUPPRESSION APPARATUS FOR POTENTIALLY
EXPLOSIVE ENVIRONMENTS**

Inventor: Thomas J. Nostrand
Express Mail Item No.: EL085013254US
Filed: *January 7*, 2002

TRANSIENT SUPPRESSION APPARATUS FOR POTENTIALLY EXPLOSIVE ENVIRONMENTS

BACKGROUND OF THE INVENTION

[0001] The present invention is directed to transient suppression devices, in general, and more particularly, to transient suppression apparatus coupleable in series with an electrical pathway into a potentially explosive environment for limiting current, voltage and energy to levels considered safe for such environments, and to systems utilizing such apparatus.

[0002] An aircraft fuel measurement or indication system is an example of a system which utilizes transient suppression devices for limiting current, voltage and energy into a potentially explosive environment. In such a system, sensors are disposed at or in the fuel tank of the aircraft and a sensor excitation system remote from the tank generates excitation signals over electrical pathways to the sensors for measuring the quantity of fuel in the tank. Currently, there are many different types of sensors, comprising capacitive, inductive and/or resistive elements, for example, and different types of excitation signals needed to excite these sensors, like alternating current (AC), direct current (DC) and/or pulsed excitation signals, for example. Because of these differing system applications, the transient suppression solutions therefor need to accommodate differing levels of current, voltage and energy protection.

[0003] In addition, recent new requirements have been specified to insure aircraft safety, specifically associated with fuel tank safety which is considered a potentially explosive environment. These requirements apply to multiple threat and failure conditions that could impose unsafe levels of energy, voltage and current into the potentially explosive fuel tank environment if left unprotected. Existing transient suppression devices which are disposed in the electrical pathways use magnetic isolation, such as inductors and/or transformers and band pass circuit filtering, for example, to limit the current, voltage and energy parameters of the electrical pathways to the fuel tank. While an adequate solution, each transient suppression device needs to be tailored or designed for a specific application or group of similar applications in order to accommodate the level of current, voltage and energy protection required therefor while maintaining the level of sensitivity of an existing solution at normal operation taking into account parasitic components of the electrical pathways.

Accordingly, there is no known existing transient suppression solution that may be universally used for the many different types of sensor/system applications and requirements therefor.

[0004] The present invention intends to overcome the drawbacks of the existing transient suppression devices and systems utilizing the same by offering substantially universal transient suppression apparatus which will provide the specified protection with different types of sensors and sensor excitation signaling and not be subject to the level of sensitivity that the existing solutions have at normal sensor measurement operation.

SUMMARY OF THE INVENTION

[0005] In accordance with one aspect of the present invention, transient suppression apparatus, which is coupleable in series with an electrical pathway into a potentially explosive environment for limiting current, voltage and energy thereto, comprises: an impedance element coupleable in series with the electrical pathway to conduct current to the potentially explosive environment, the current causing a voltage potential across said impedance element; at least one first semiconductor element coupled to the impedance element in series with the current path upstream of the impedance element, the at least one first semiconductor element operative to impose a resistance to the current of the electrical pathway governed by the voltage potential across the impedance element; and at least one second semiconductor element coupled to the impedance element in series with the current path downstream of the impedance element, the at least one second semiconductor element operative to impose a series resistance to the current of the electrical pathway governed by the voltage potential across the impedance element.

[0006] In accordance with another aspect of the present invention, a system for determining a quantity of fuel in a container comprises: at least one sensor disposed at the container for sensing a quantity of fuel in the container; sensor excitation system coupled to each of the at least one sensor through an electrical pathway for providing an excitation signal thereto; transient suppression apparatus as described directly above disposed in series with each electrical pathway for limiting current, voltage and energy to the container.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Figure 1 is an exemplary system application of an embodiment of the present invention.

[0008] Figure 2 is a circuit schematic of a transient suppression device suitable for embodying the present invention.

[0009] Figure 3 is a graph illustrating the impedance characteristics of a semiconductor device suitable for use in the embodiment of Figure 2.

[00010] Figure 4 is circuit schematic of an alternate transient suppression device suitable for embodying the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[00011] The present embodiment of the invention is described, by way of example, in connection with a fuel quantity measuring system for one or more aircraft fuel tanks such as that shown by the illustration of Figure 1. However, it is understood that this fuel measurement system is but one example of a potentially explosive environment and that there are many other such environments that are just as suitable for embodying the present invention. Therefore, the transient suppression apparatus of the present invention should not be limited to any specific potentially explosive environment, but rather intended for use in all possible environments which are potentially explosive by nature.

[00012] Referring to Figure 1, the system 10 as illustrated is intended for use on-board an aircraft which includes at least one fuel tank 12 having a quantity of aircraft fuel 14. At least one sensor is disposed at or in the fuel tank 12 for measuring the quantity of the fuel 14 therein. In the present embodiment, a plurality of sensors S1, S2, . . . , Sn, which may include capacitive elements are disposed in the fuel tank 12 for measuring the fuel quantity therein. While capacitive type sensors are used for describing the present embodiment, it is understood that inductive or ultrasonic pulse or a combination of sensor types may be used just as well. A conventional sensor excitation system 16 is disposed at a remote location from said fuel tank and is operative to generate excitation signals which are conducted to each sensor S1, S2, . . . , Sn over respectively corresponding electrical pathways P1, P2, . . . , Pn which are coupled respectively to the sensors S1, S2, . . . , Sn. The excitation signals may be any one of the group of signals comprising AC, DC and pulsed excitation signals depending on the type of sensor being excited thereby. Transient suppression devices TSD1, TSD2, . . . , TSDn are disposed respectively in series with each pathway P1, P2, . . . , Pn for limiting current, voltage and energy to the container 14 from each such pathway.

[00013] A suitable embodiment of a transient suppression device (TSD) in accordance with the present invention is shown in the circuit schematic of Figure 2. The TSD of Figure 2 is coupleable in an electrical pathway as described in connection with the exemplary

embodiment of Figure 1. In the present example, the electrical pathway includes a supply path 20 and a return path 22 over which current 18 may be conducted between the system 16 and sensor Si (i being 1, 2, . . . , or n). Referring to Figure 2, an impedance element 24 is coupleable in series with the path 20 of the electrical path to conduct current into the electrically explosive fuel environment of the fuel tank 12. The current conducted to the tank 12 causes a voltage potential across the impedance element 24. In the present embodiment, the impedance element comprises a resistive element, but it is understood that other impedance elements or combinations thereof could also be used in certain applications. At least one semiconductor element 26, which may be a field effect transistor (FET), for example, is coupled to the impedance element 24 in series with the current path 18 upstream of the impedance element 24. In this embodiment, only one semiconductor element 26 is used. An embodiment using more than one semiconductor element or a plurality will be described herein below in connection with the circuit schematic of Figure 4.

[00014] More specifically, in Figure 2, the FET 26 has its current channel S-D connected in series with the impedance element 24 in the path 20 and its gate G connected to a circuit node 28 at the downstream side of the impedance element 24. Accordingly, the voltage potential across the impedance element 24 is what governs the resistance of the current channel of the FET 26 which is in series with the electrical pathway. The resistance to voltage characteristics of the FET 26 are exemplified in the graph of Figure 3. Referring to the graph of Figure 3, note that as the channel to gate voltage of the FET (which is the voltage potential across the impedance element 24) varies at a first or positive polarity, the resistance of the current channel of the FET varies proportionately therewith as shown by the solid line 30 until it reaches a substantially open circuit condition at the voltage differential shown by the dashed line 32. However, at around zero differential voltage or differential voltages at a second or negative polarity, the resistance of the current channel remains substantial low. A positive polarity of voltage potential for the present example refers to current 18 in a direction from left to right or upstream to downstream through the impedance element 24 and a negative polarity of voltage potential would refer to current in the reverse direction.

[00015] Referring back to the schematic of Figure 2, another at least one semiconductor element 34, which may also be an FET, for example, is coupled to the impedance element 24 in series with the current path 18 downstream of the impedance element 24 at node 28. Thus, the current channel S-D of the FET 34 is connected in series with the impedance element 24 in the path 20 and its gate G connected to a circuit node 36 at the upstream side of the

impedance element 24. Accordingly, the voltage potential across the impedance element 24 also governs the resistance of the current channel of the FET 34 which is in series with the electrical pathway. The resistance to voltage characteristics of the FET 34 may also be exemplified by the graph of Figure 3 except now the polarity is reversed. That is, as the channel to gate voltage of the FET 34 (which is the voltage potential across the impedance element 24) varies at a second or negative polarity, the resistance of the current channel of the FET 34 varies proportionately therewith as shown by the solid line 30 until it reaches a substantially open circuit condition at the voltage differential shown by the dashed line 32. However, at around zero differential voltage or differential voltages at a first or positive polarity, the resistance of the current channel remains substantial low.

[00016] Also, in the embodiment of Figure 2, one or more series connected voltage potential surge suppression elements 38 and 40 may be coupled in parallel with the electrical pathway across paths 20 and 22 upstream and downstream of the TSD circuit described herein above, respectively. The surge suppression elements 38 and 40 may be of the type manufactured by Microsemi bearing model number SMCJ170CA, for example., which are capable of protecting the TSD against voltage surges of up to approximately 200 volts each or 600 volts if three (3) in series are used, for example. Also, the semiconductor elements 26 and 34 may be metal oxide semiconductor field effect transistors (MOSFETs) of the type manufactured by Infineon bearing model number BSP-149, for example, which are capable of withstanding blocking voltages of approximately 200 volts each, for example.

[00017] Prior to installation of the TSD into its designated electrical pathway, the impedance element 24 is selected based on the particular sensor and sensor excitation signal which it will accommodate under normal operating conditions. This impedance should be small enough so as to effect a voltage drop across element 24 which does not affect appreciably the sensor measurement under normal operating conditions, but large enough to effect a voltage drop which will maintain the transistors 26 and 34 biased "on" under such conditions. For most applications, a resistance of on the order of one hundred ohms (100Ω), for example, may be used for the impedance element. When biased "on", the transistors 26 and 34 each provide a small series resistance in the current pathway as illustrated by the exemplary characteristics of Figure 3. The series resistance of the transistors 26 and 34 and the resistance of the element 24 should be selected so as to not affect the performance of the sensor measurements or system operation under normal operating conditions.

[00018] When a TSD is disposed in an electrical pathway to a potentially explosive environment, if an external threat, such as a lightning induced voltage, electromagnetic

interference (EMI) induced energy or the like, for example, or a failure of the electrical pathway to a power line which may be 115V, 400 Hz or 28 VDC, for example, or a latent failure condition that may emulate a current or voltage path to ground potential in the fuel tank should occur, the TSD will regulate and limit the current, voltage and energy to the environment to specified safe levels. During a threat or failure condition, an increase in the current 18 through the element 24 will cause a voltage potential across element 24 that governs at least one of the transistors 26 and 34 to start to shut "off", i.e. become blocking or non-conducting, which increases the series resistance thereof to the current path. Under such abnormal conditions, the transistors 26 and 34 act as non-linear resistors which regulate the current into the potentially explosive environments, or in the case of the present embodiment, the aircraft fuel tank 14. This current into the potentially explosive environment remains limited to safe levels by the TSD even in the face of increasing external voltage or current threats. For example, the energy and current may be limited to less than 200 microjoules (μJ) of energy and 20 milliamps (mA) of current into the fuel tank or environment in some cases. Also, each transistor is capable of blocking voltages of on the order of 200 volts, for example. Abnormal voltage may be also limited by the surge suppression elements 38 and 40 to voltage levels of 600 volts, for example, where three such devices in series are used.

[00019] The TSD operates in response to threats and failures inducing increasing current 18 of both positive and negative polarities. For example, as the current 18 is increased abnormally with the first or positive polarity, the series resistance of transistor 26 is governed to increase by the polarity of the voltage potentially induced across the element 24 and thus, regulates current 18 to safe levels. The resistance of the transistor 34 remains at a relatively low value because the voltage potential across the element 24 governs the transistor 34 with the reverse polarity to that of the transistor 26 (refer to Figure 2). Also, as the current 18 is increased abnormally with the second or negative polarity, the series resistance of transistor 34 is governed to increase by the polarity of the voltage potential across element 24 and thus, regulates current 18 to safe levels. The resistance of the transistor 26 remains at a relatively low value because the voltage potential across the element 24 governs the transistor 26 with the reverse polarity to that of the transistor 34 (refer to Figure 2).

[00020] Note that each of the transistors 26 and 34 of the embodiment of Figure 2 is intended to represent one or more semiconductor elements each of which being operative to vary its blocking resistance to current 18 of the corresponding electrical pathway in response to a variation of the voltage potential across the impedance element 24. The blocking resistance of the at least one semiconductor element represented by element 26 is varied by a

voltage potential across the element 24 of a first or positive polarity and the blocking resistance of the at least one semiconductor element represented by element 34 is varied by a voltage potential across the element 24 of a second or negative polarity. A suitable embodiment for a TSD having a plurality of semiconductor elements both upstream and downstream of the impedance element 24 is illustrated in the circuit schematic of Figure 4.

[00021] Referring to Figure 4, the plurality of semiconductor elements represented by transistor 26 comprises field effect transistors Q1-Q4 which have their current channels coupled in series upstream of the element 24 between the input of the path 20 of the TSD and the node 36, Q4 being coupled to node 36 and Q1 being coupled to the input node. The gate of transistor Q4 is coupled directly to node 28 and the gates of transistors Q1 through Q3 are coupled to node 28 through resistors R10, R9 and R2, respectively. Voltage potential limiting circuit elements Z10, Z9 and Z2 are coupled respectively, anode-to-cathode, between the gates and current channels of transistors Q1 through Q3. The circuit elements Z10, Z9 and Z2 may be conventional transient suppression type zener diodes capable of limiting voltage potentials of on the order of fifteen (15) volts, for example. Also in Figure 4, the plurality of semiconductor elements represented by transistor 34 comprises field effect transistors Q5-Q8 which have their current channels coupled in series downstream of the element 24 between the output of the path 20 of the TSD and the node 28, Q5 being coupled to node 36 and Q8 being coupled to the output node. The gate of transistor Q5 is coupled directly to node 36 and the gates of transistors Q6 through Q8 are coupled to node 36 through resistors R16, R13 and R11, respectively. Voltage potential limiting circuit elements Z16, Z13 and Z11 are coupled respectively, anode-to-cathode, between the gates and current channels of transistors Q6 through Q8. The circuit elements Z16, Z13 and Z11 may be conventional transient suppression type zener diodes capable of limiting voltage potentials of on the order of fifteen (15) volts, for example.

[00022] Accordingly, the channel resistances of transistors Q1-Q4 which may be MOSFETs, for example, are operational to block abnormal currents 18 which induce a positive polarity voltage potential across element 24 and thus, block abnormal voltages of a positive polarity and limit the current, voltage and energy to the potentially explosive environment under adverse threat and failure conditions. Likewise, the channel resistances of transistors Q5-Q8 which also may be MOSFETs, for example, are operational to block abnormal currents 18 which induce a negative polarity voltage potential across element 24 and thus, block abnormal voltages of a negative polarity and limit the current, voltage and energy to the potentially explosive environment under adverse threat and failure conditions.

The zener-resistor pairs Z10-R10, Z9-R9 and Z2-R2 protect the channel to gate junctions of transistors Q1, Q2 and Q3 respectively, by limiting the voltage potential thereacross.

Similarly, zener-resistor pairs Z16-R16, Z13-R13 and Z11-R11 protect the channel to gate junctions of transistors Q6, Q7 and Q8 against over voltage in the same manner. In an operating environment in which a large amount of EMI is anticipated, some additional EMI filtering may be added to the transient suppression circuit at both the input and output thereof.

[00023] While the present invention has been described by way of example in connection with one or more embodiments herein above, it is understood that it should not be limited in any way, shape or form to such embodiments. Rather the present invention should be construed in breadth and broad scope in accordance with the recitation of the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187